



SAFETY DATA SHEET

PAVETUF JOINTING GROUT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Jointing Grout
--------------	----------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC1] Adhesives, sealants; [PROC8a] Transfer of substance or preparation (charging/discharging) from/to vessels/ large containers at non-dedicated facilities;
Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company	Talasey Ltd
Address	ST VINCENT HOUSE NORMANBY ROAD SCUNTHORPE DN15 8QT
Web	www.talasey.co.uk
Telephone	+44 (0)330 333 8030
Fax	+44 (0)330 333 8040
Email	sales@talasey.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Main hazards	No Significant Hazard
--------------	-----------------------

2.3. Other hazards

Other hazards	Product contains biocide to protect the cured product from microbial attack.
---------------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica Sand		14808-60-7	238-878-4		10 - 20%	
Calcium Sulphate Hemihydrate (Plaster of Paris total inhalable dust)		2649-65-0	231-900-3		1 - 10%	
2-Octyl-2H-isothiazol-3-one	613-112-00-5	26530-20-1	247-761-7		0 - 0.5%	T; R23/24 Xn; R22 C; R34 R43 N; R50/53

PAVETUF JOINTING GROUT

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Calcium Sulphate Hemihydrate (Plaster of Paris respirable dust)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 4 WEL 15 min limit mg/m3: -
Calcium Sulphate Hemihydrate (Plaster of Paris total inhalable dust)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: -
Silica Sand	WEL 8-hr limit ppm: WEL 15 min limit ppm:	WEL 8-hr limit mg/m3: 0.3 WEL 15 min limit mg/m3:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
---	--

PAVETUF JOINTING GROUT

8.2. Exposure controls

8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles.
Skin protection - Hand protection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Powder
Colour	Various
Solubility	Slightly soluble in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations. Do not allow product to enter drains. Do not flush into surface water.
--	--

SECTION 14: Transport information

ADR/RID

	The product is not classified as dangerous for carriage.
--	--

IMDG

	The product is not classified as dangerous for carriage.
--	--

IATA

	The product is not classified as dangerous for carriage.
--	--

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

Labelling

Risk phrases	No Significant Hazard.
--------------	------------------------

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 1 - Description. 2 - Other hazards. 13 - General information.
Text of risk phrases in Section 3	R22 - Harmful if swallowed. R23/24 - Toxic by inhalation and in contact with skin.

PAVETUF JOINTING GROUT

8.2. Exposure controls

	R34 - Causes burns. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--