




# SATIN SEALER



**EASY TO APPLY  
SEALER, FOR LONG  
LASTING PROTECTION  
WITH A SATIN FINISH**



Satin Sealer is a breathable UV stable, penetrating sealer giving protection and an enhanced appearance to porous landscaping areas. Giving excellent water and oil repelling properties, it protects against the main causes of degradation and oxidation, helping to delay the ageing process. Satin Sealer is a non-film forming impregnating treatment. This advanced water based formula allows you to seal your paving immediately after installation and allows efflorescence/salts and moisture to pass from the mortar bed through the paving. This sealer is an environmentally friendly product, completely waterborne, non toxic, solvent and silicone free.

#### BENEFITS

- Delays the penetration of water and oily liquids allowing time to clean up any spillage to prevent staining
- UV resistant
- Non-flammable
- Non-toxic
- Environmentally friendly
- Non hazardous

#### APPLICATION

Not suitable if surfaces have been treated previously with a silicone or stearate-based water repellent.

Always test a small inconspicuous area before proceeding to ensure the finished result is satisfactory and to identify the optimum number of coats required.

Do not dilute or mix with other products.

Ensure the surface is completely clean, dry, and free from dirt, grime, cement, and grout. If necessary, first wash surfaces with a dilute solution of Pavetuf Deep Cleaner 1:5 and scrub with a white nylon pad. Rinse well to remove residues and leave to dry.

Do not walk on treated surfaces until the solution has completely dried.

Shake the container well before use.

Work in small areas when applying Satin Sealer as multiple coats may be required depending on how porous your product is.

Satin Sealer is water based and the product must be applied until saturation is achieved to ensure 100% product efficiency. You must not let Satin Sealer dry between coats, each extra coat needs to be reapplied before the previous coat dries, wet on wet.

Apply evenly using a foam roller, paint brush or low pressure pump sprayer.

On vertical surfaces always apply from the bottom up and wipe up any drips if they occur.

Product will normally be touch dry within 1-6 hours, allow longer in colder conditions. Drying time 24 hours. Optimum performance is reached after 3 days.

#### STORAGE INFORMATION

Use within 24 months from the date of manufacture.

Store in the original unopened container in a clean, dry area and ideally at 5°C - 25°C (41°F - 77°F)



Distributed worldwide by Talasey Ltd  
[www.talasey.co.uk](http://www.talasey.co.uk)

#### RECOMMENDATIONS

Do not apply during wet weather, frost or if rain is forecast. Do not use in temperatures under 5°C or over 25°C (41°F - 77°F).

Please be aware darker coloured paving will have a considerably higher surface temperature in warmer weather conditions.

This product is not designed for non-absorbent surfaces.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

Please dispose of packaging and waste products in line with current environmental legislation.

#### COVERAGE PER COAT

	1LTR(33.8floz)	5LTR(169.1floz)
Medium porosity surfaces	15m <sup>2</sup> (160 ft <sup>2</sup> )	75m <sup>2</sup> (800 ft <sup>2</sup> )
Higher porosity surfaces	7.5m <sup>2</sup> (80 ft <sup>2</sup> )	37.5m <sup>2</sup> (400 ft <sup>2</sup> )
Honed surfaces	30m <sup>2</sup> (320 ft <sup>2</sup> )	150m <sup>2</sup> (1600 ft <sup>2</sup> )

HEALTH, SAFETY & ENVIRONMENTAL  
KEEP OUT OF THE REACH OF CHILDREN.



5060393100003



HDPE

MANUFACTURED IN THE UK

Disclaimer: Pavetuf Satin Sealer, if used in accordance with the instructions provided, should produce results as described. Talasey Ltd does not offer nor imply any guarantees. No liability will be accepted from either the supplier nor the manufacturer, for changes in appearance or markings of the material on which it is used. Revised SSPL0623V1

Before use, please read the safety data sheet available on  
[www.pavetuf.com](http://www.pavetuf.com)

For further information or technical advice call  
☎ 0330 333 8030 or ☎ (888) 240 8704